



Pillar stand type, 2 X-LED3 illuminator arms & 60 chip LED disc trans-illuminator

Focusing System	Type	Coarse
	Coarse total travel (mm)	50
	Adjustable tension	Yes
	Head holder internal diameter (mm)	76
Stand	Type	Pillar
	Pillar diameter (mm)	32
Stage	White diffusion plate for transmitted ill.	Yes, diameter 100 mm
	Specimen clips	Yes
Transmitted Illumination	Type	X-LED
	X-LED type	X-LEDT3
	Light source power (W)	4
	Illuminance (lux)	8,000
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
Max. required power (W)	5	
Incident Illumination	Type	X-LED
	X-LED type	X-LED3 (double arm)
	Light source power (W)	7.2
	Illuminance (lux)	170,000
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
Max. required power (W)	9.6	
Power Supply for Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	12 Vdc 1.5 A
Accessories Included	Dust cover	Yes
	User Manual	Digital version (downloadable)
Product Dimensions	Total height (mm)	315
	Base height (mm)	30
	Base width (mm)	210
	Base depth (mm)	270
Product Weight	(kg)	2.7